

CONDOPLEX

2700 Panel



- Aesthetically designed slim-lined panel with tactile response silicone keypad
- Advanced on-board microprocessor
- Programmability at master and service levels
- Two-wire data and audio connection, and BNC video connection
- 4 supervised hard wire zones (expandable to 8)
- Open or closed programmable zone contacts
- Zones can have one or two resistor supervision
- Instant Mode by-passes interior zones
- Memory stores alarm and zone status
- Nine traceable User Codes plus Duress Code
- Adjustable intercom and beep volume control
- Separate function keys for Panic, Emergency, Programming, Instant Mode, Shunt Mode and Intercom
- Separate front/back door bells with unique tones and controllable chimes

Specifications:

Input Power	12 VDC @ 35 mA, reverse protected, 2-wire min. 18 AGW	Video	BNC connector, 75 ohms impedance, NTSC, RG59 cable Available in 4" CRT B/W or 4" TFT Color Spark gap on all inputs and outputs. Diode protection on audio and data lines. MOV protection on data lines.
Siren (Speaker)	Audio and multi-tone, 700 mW speaker, 75 dB when siren ON	Transient and Lightning Protection	
Alarm Output	Open collector, max. 100 mA	Maximum Number Units	5 per suite (1 master and 4 slaves)
Loop Type	Entry/Exit, Interior, Perimeter, Panic, Emergency, Fire	Accessories	4 zone expander, Re1, Re2
Loop Response Time	Programmable, 100 msec to 1.5 sec	Mounting Requirements	2700BB (Back Box), 4 tamper-proof screws
Loop Resistance	Programmable 4 state loop, NC loop and NO loop [4 state = 1 K ohms (normal), 2 K ohms (alarm), open or short (trouble)]	Dimensions	19.69 cm (W) x 21.27 cm (H) x 6.35 cm (D) 7.75 in (W) x 8.38 in (H) x 2.5 in (D)
Display	8 status LED's	Shipping Weight	1.2 Kg (2 lb 10 oz)
Communication Format	RS485, 2-wire twisted direct connection to CPLX-4	Operating Temperature	0°C to 50°C (-32°F to 132°F)
Audio Input	150 ohms impedance, 2-wire awg twisted pair	Ordering Information	2700C for Color 2700B for B/W

condoplex monitoring systems inc.

integrated security products
22 Constellation Court
Etobicoke, Ont. M9W 1K1
phone: (416) 674-9800
fax: (416) 213-1411
<http://www.condoplex.net>
<http://www.condoplexinc.com>

specifications subject to change without notice

04/03